

AUSTRALIA GHS Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: FUSOR 122EZ SELF-LEVELING SEAM SEALER PT A
Product Use/Class: ADHESIVE, PART A

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtree 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

Connell Bros. Co. Australasia Pty Ltd. Unit 3 / 257 Leitchs Road Brendale QLD 4500 Australia ABN 53 079 159 327

Telephone: 07 3552 9200

Australia Wide - 24 Hr Emergency Number

1800-033-111

EFFECTIVE DATE: 08/04/2022

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Acute toxicity DermalCategory 5 - 95.4% of the mixture consists of ingredient(s) of unknown toxicity.

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Skin sensitization Category 1

Reproductive toxicity Category 2

Hazardous to the aquatic environment - acute hazard Category 2

Hazardous to the aquatic environment - chronic hazard Category 2

GHS LABEL ELEMENTS:

Symbol(s)







Signal Word

WARNING

Hazard statements

May be harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

Page 1 of 7

Precautionary statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, eye protection, face protection.

Use personal protective equipment as required.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Response

Call a POISON CENTER or doctor, physician if you feel unwell.

Specific treatment (see supplemental first aid instructions on this label).

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice, attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash before reuse.

Collect spillage.

Storage

Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Dermal absorption possible. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range	
Epoxy resin	1675-54-3	55 - 60 %	
Alkyl phenol blocked polyisocyanate	Proprietary	15 - 20 %	
Epoxy resin	Proprietary	10 - 15 %	
Epoxy resin	Proprietary	5 - 10 %	
Alkyl (C12-14)glycidyl ether	68609-97-2	1 - 5 %	
4-Nonyl phenol	84852-15-3	0.1 - 0.9 %	
Epoxy resin	1675-54-3	0.1 - 0.9 %	

Epoxy resin (1675-54-3) can also be represented by CAS 25068-38-6.

4. FIRST AID MEASURES

Product: FUSOR 122EZ SELF-LEVELING SEAM SEALER PT A, Effective Date: 08/04/2022

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry chemical, Foam, Water fog **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Keep container tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self contained breathing apparatus. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Avoid contact. Avoid breathing vapors. Use appropriate respiratory protection for large spills or spills in confined area.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of this safety data sheet. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.; Strong acids, bases, and strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

08/04/2022

COMPONENT EXPOSURE LIMIT

Epoxy resin	1675-54-3	Not established
Alkyl phenol blocked polyisocyanate	PROPRIETARY	Not established
Epoxy resin	PROPRIETARY	Not established
Epoxy resin	PROPRIETARY	Not established
Alkyl (C12-14)glycidyl ether	68609-97-2	Not established
4-Nonyl phenol	84852-15-3	Not established
Epoxy resin	1675-54-3	Not established

ENGINEERING CONTROLS: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

Respiratory protection: Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

Skin protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

Eye protection: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

Other protective equipment: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Hygienic practices: Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

Coefficient of water/oil distribution:

Vapor Pressure: **Epoxy** N.D. Appearance: Vapor density: Heavier than Air Clear Physical state: Liquid Lower explosion limit: Not applicable Flash point: ≥ 201 °F, 93 °C Upper explosive limit: Not applicable Setaflash Closed Cup **Boiling range: Evaporation rate:** Slower than n-butyl-N.A. acetate Autoignition temperature: N.D. Density: 1.13 g/cm3 **Decomposition temperature:** Viscosity, dynamic: N.D. N.D. **Odor threshold:** Viscosity, kinematic: N.D. N.D. Solubility in H2O: Insoluble Volatile by weight: 0.00 % pH: N.A. Volatile by volume: 0.00 % **VOC Calculated:** 0 lb/gal, 0 g/l0 g/l Freeze point: N.D.

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

N.D.

10. STABILITY AND REACTIVITY

Product: FUSOR 122EZ SELF-LEVELING SEAM SEALER PT A, Effective Date:

08/04/2022

HAZARDOUS POLYMERIZATION: Hazardous polymerisation will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.; Strong acids, bases, and

strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes.

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

CHRONIC EFFECTS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Acute toxicity Dermal: Category 5 - May be harmful in contact with skin. Components contributing to classification: Alkyl (C12-14)glycidyl ether.

Chemical Name	<u>LD50/LC50</u>
Epoxy resin	Dermal LD50: Rabbit 20,000 mg/kg
Alkyl phenol blocked polyisocyanate	N.D.
Epoxy resin	N.D.
Epoxy resin	N.D.
Alkyl (C12-14)glycidyl ether	Oral LD50: Rat 17,100 mg/kg Dermal LD50: Rabbit > 3,987 mg/kg
4-Nonyl phenol	Oral LD50: Rat 1,300 mg/kg Dermal LD50: Rabbit 2,000 mg/kg
Epoxy resin	Dermal LD50: Rabbit 20,000 mg/kg

Skin corrosion/irritation: Category 2 - Causes skin irritation.

Components contributing to classification: Epoxy resin. Epoxy resin. Alkyl (C12-14)glycidyl ether.

Serious eye damage/eye irritation: Category 2A - Causes serious eye irritation.

Components contributing to classification: Epoxy resin. Epoxy resin. Alkyl (C12-14)glycidyl ether.

Skin sensitization: Category 1 - May cause an allergic skin reaction.

Components contributing to classification: Epoxy resin. Epoxy resin. Alkyl (C12-14)glycidyl ether. Epoxy resin.

Respiratory sensitization: No classification proposed

Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child.

Components contributing to classification: 4-Nonyl phenol.

Specific target organ systemic toxicity (single exposure): No classification proposed

Product: FUSOR 122EZ SELF-LEVELING SEAM SEALER PT A, Effective Date:

08/04/2022

Specific target organ systemic toxicity (repeated exposure): No classification proposed

Aspiration hazard: No classification proposed

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
Epoxy resin	Invertebrates: Daphnia magna 1.7 mg/l48 h
Alkyl phenol blocked polyisocyanate	N.D.
Epoxy resin	N.D.
Epoxy resin	N.D.
Alkyl (C12-14)glycidyl ether	N.D.
4-Nonyl phenol	Fish: Pimephales promelas 0.135 mg/l96 h Flow through Lepomis macrochirus 0.1351 mg/l96 h Flow through Invertebrates: Daphnia magna 0.14 mg/l48 h Plants: Pseudokirchneriella subcapitata 0.36 - 0.48 mg/l96 h Static Pseudokirchneriella subcapitata 0.16 - 0.72 mg/l72 h Static Desmodesmus subspicatus 1.3 mg/l72 h
Epoxy resin	N.D.

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

14. TRANSPORT INFORMATION

IATA Cargo

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Hazard Class: 9
Hazard class: None
UN number: 3082
Packing group: III
EmS: 9L

IMDG

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Hazard Class: 9
Hazard class: None
UN number: 3082
Packing group: III
EmS: F-A; S-F

Product: FUSOR 122EZ SELF-LEVELING SEAM SEALER PT A, Effective Date: 08/04/2022

The listed transportation classification applies to IATA Cargo and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors for your country or particular locality. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS: AS FOLLOWS -

AUSTRALIA INVENTORY OF EXISTING CHEMICAL SUBSTANCES (AICS):

All components of this product are on the AICS list.

16. OTHER INFORMATION

Revision: Section 1

Effective Date: 08/04/2022

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.